



CS-8810

Single Needle, Needle Feed & Top/Bottom Roller Feed, Postbed Sewing Machine.

Model No. CS-8810		S.P.M. 2,500	
Max.Stitch Length 7mm	Lift Of Roller Presser (Knee) 15mm		
Needle System DP×5 #16 (#14~#19)	Needle Bar Stroke 38mm		

Due to special unison feed(needle feed & top/bottom roller feed) , no wrinkle in light material and fine stitch in heavy material.

- Maintenance-free ball and needle bearings and link type of thread take-up lever.
- Applied full rotating vertical axis of rotary hook with positive bobbin case opener.
- Equipped with easy-operating safety clutch which would protect rotating hook from damage.
- For sewing functional and ornamental seams preferably on concave portions of shoe uppers, leather products,etc..

CS-8810

D

G

Model:

Single Needle, Needle Feed & Top/Bottom Roller Feed, Postbed Sewing Machine.

Code Description:

: Basic Type
D: With Direct Drive Servo Motor

Code Description:

: Standard Hook
H: For Thick Thread Stitching. (Standard hook)
G: Large Hook



CS-861

Single Needle, Needle Feed & Top/Bottom Roller Feed, Postbed Sewing Machine.

SPECIFICATIONS:

Model No.	Max. Sewing Speed S.P.M.	Lifting Of Roller Presser (Knee) mm	Max. Stitch Length mm	Needle Bar Stroke mm	Hook System	Needle System
CS-8810	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)
CS-8810D	2500	15	7	38	Standard Hook	
CS-8810G	2500	15	7	38	Large Hook	DP×17 or LY128GAS (#23~#25)
CS-8810H	1500	15	7	38	Standard Hook	

CS-8810D



Single Needle, Needle Feed & Top/Bottom Roller Feed, Postbed Sewing Machine. (With direct drive servo motor)

- Applied with direct drive servo motor, ensured high sewing efficiency & electricity saving.

CS-8810H



Single Needle, Needle Feed & Top/Bottom Roller Feed, Postbed Sewing Machine. (For thick thread stitching)

- For thick thread stitching, up to #0 (3×4) thick thread.