



IRONING LINE

COD. BF048

# AUTOMATIC VAPOR

Steam generator with automatic refilling system for ironing

- 1 CORD HOLDING ROD
- 2 PROFESSIONAL IRON
- 3 SWITCHES FOR IRON AND HEATERS
- 4 TANK FOR AUTOMATIC REFILL



## TECHNICAL DATA

POWER	220V-240V 50-60Hz
BOILER CAPACITY	2,8 lt
BOILER POWER	900W+900W
STEAM PRESSURE	3 Bar
BOILER REFILL	AUTOMATIC
IRON POWER	850W
DIMENSIONS	26,5x32xh82,5 cm
WEIGHT	18 kg

## AVAILABLE VERSIONS

BF048BE "AUTOMATIC VAPOR"	900W+900W 230V, BIEFFE IRON 1,5 KG
BF048CE "AUTOMATIC VAPOR"	900W+900W 230V, "HEAVY" BIEFFE IRON 1,7 KG

## AVAILABLE ACCESSORIES

<b>AR25</b> Steam gun round nozzle 1 exit	<b>AR252V</b> Steam gun round nozzle 2 exit	<b>AR115</b> Steam brush "Speedy" 500W	<b>BF011</b> Sleeve board	<b>AR14</b> Armored teflon base	<b>AR153</b> Talc spray stain remover	<b>AR9</b> Iron cleanser stick
<b>SIMPLE TEFLON SHOE</b> 1,5 kg <b>AR8</b> 1,7 kg <b>AR8G</b>	<b>BORDERED TEFLON SHOE</b> 1,5 kg <b>AR8S</b> 1,7 kg <b>AR8V</b>	<b>ARMOURD TEFLON SHOE</b> 1,5 kg <b>AR8P</b> 1,7 kg <b>AR8C</b>	<b>AR29</b> Iron cleanser paste	<b>AR86</b> Iron cleanser mat	<b>AR134</b> Velvet mat for ironing 700x300mm	

## EFFICIENCY, SAFETY and NOTES

- ✓ RELIABILITY AND SAFETY are guaranteed by a COPPER BOILER. Copper is an explosion-proof and antiscaling material. The HEATERS are placed externally, so they NEVER come into contact with water.
- ✓ 1 KW power creates a steam flow equal to 1,2 kg/h (20 g/min). The efficiency of steam is proportional to its flow, not to its pressure. There is no point in having high pressure and a low flow.
- ✓ The whole production is based in Italy, in our plant in Pesaro.

## SPARE PARTS AND SERVICE

- BIEFFE guarantees the shipping of spare parts, accessories in very short times. Our efficient help line is available for service and assistance.
- For spare parts and service: [info@bieffeitalia.it](mailto:info@bieffeitalia.it)
- Visit our website: [www.bieffeitalia.it](http://www.bieffeitalia.it)