



CS-8820

Double Needle, Top & Bottom Roller Feed, Postbed Sewing Machine.

Model No. CS-8820		S.P.M. 2,500	
Max. Stitch Length 4mm	Lift Of Roller Presser (Knee) 15mm		
Needle System DP×5 #16 (#14~#19)	Needle Bar Stroke 41mm		

Owing to the combination of top & bottom roller feed (driven roller presser and wheel feed), no wrinkle in light material and fine stitch in heavy material.

- Maintenance-free ball and needle bearings and link type of thread take-up lever.
- Applied full rotating vertical axis of rotary hook with positive bobbin case opener.
- Equipped with easy-operating safety clutch which would protect rotating hook from damage.
- Standard needle gauge: 1.6mm or 2.0mm or 2.4mm
- For sewing functional and ornamental seams preferably on concave portions of shoe uppers, leather products,etc..

CS-8820

D

G

Model:

Double Needle, Top & Bottom Roller Feed, Postbed Sewing Machine.

Code Description:

: Basic Type
D: With Direct Drive Servo Motor

Code Description:

: Standard Hook
H: For Thick Thread Stitching. (Standard hook)
G: Large Hook



CS-862

Double Needle, Top & Bottom Roller Feed, Postbed Sewing Machine.

SPECIFICATIONS:

Model No.	Max. Sewing Speed S.P.M.	Lifting Of Roller Presser (Knee) mm	Max. Stitch Length mm	Needle Bar Stroke mm	Hook System	Needle System
CS-8820	2500	15	4	41	Standard Hook	DP×5 #16 (#14~#19)
CS-8820D	2500	15	4	41	Standard Hook	
CS-8820G	2500	15	4	41	Large Hook	DP×17 or UY128GAS#23
CS-8820H	1500	15	4	41	Standard Hook	

CS-8820G



Double Needle, Top & Bottom Roller Feed, Postbed Sewing Machine. (Large hook)

- Applied with large hook ensured high sewing efficiency.

CS-8820H



Double Needle, Top & Bottom Roller Feed, Postbed Sewing Machine. (For thick thread stitching)

- For thick thread stitching, up to #5 (3×2) thick thread.
- Standard needle gauge: 2.4mm.